

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in this application:

Claim 1 (original): A bandwidth-adaptive method for synchronizing display data between a source node and a plurality of consumer nodes, the method comprising the steps of:

- (a) identifying, by a source node, a change in local display data;
- (b) creating, by the source node, at least one data packet representing the change in local display data;
- (c) receiving, from the source node, metadata information identifying at least one data packet representing the current state of local display data;
- (d) receiving, from the source node, at least one of the identified data packets;
- (e) selecting at least one of the received data packets responsive to the received metadata information;
- (f) transmitting to a consumer node the metadata information; and
- (g) transmitting to the consumer node the selected at least one data packet.

Claim 2 (original): The method of claim 1 further comprising the step of, before step (e), receiving a request from a consumer node for the current state of the source node local display data.

Claim 3 (currently amended): The method of claim 2 further comprising the step of repeating steps (a) through (d) until ~~a~~the request is received from ~~a~~the consumer node for the current state of the ~~changing data set~~source node local display data.

Claim 4 (original): The method of claim 3 wherein step (e) comprises the steps of:

(e-a) selecting one of the received metadata information; and

(e-b) selecting at least one of the received data packets identified by the selected metadata information.

Claim 5 (original): The method of claim 1 wherein step (e) comprises selecting a plurality of the received data packets responsive to the received metadata information.

Claim 6 (currently amended): The method of claim 5 wherein step ~~(f)~~(g) comprises transmitting to athe consumer node each of the selected plurality of data packets.

Claim 7 (original): The method of claims 1 wherein step (d) comprises receiving from the source node at least one of the identified data packets in encrypted form.

Claim 8 (original): The method of claim 1 further comprising the step of storing the received metadata information in a memory device.

Claim 9 (original): The method of claim 1 further comprising the step of storing the received at least one data packet in a memory device.

Claim 10 (original): The method of claim 9 wherein step (e) comprises:

(e-a) selecting at least one of the received data packets responsive to the received metadata information; and

(e-b) selecting at least one of the stored data packets responsive to the received metadata information.

Claim 11 (original): The method of claim 10 where step (g) comprises:

(g-a) transmitting to the consumer node the selected at least one of the received data packets; and

(g-b) transmitting to the consumer node the selected at least one of the stored data packets.

Claim 12 (original): The method of claim 1 further comprising the step of storing, in a memory element, information identifying the at least one data packet transmitted to the consumer node.

Claim 13 (original): The method of claim 12 further comprising the step of selecting at least one of the received data packets responsive to the received metadata information and the stored information identifying the at least one data packet transmitted to the consumer node.

Claim 14 (currently amended): A bandwidth-adaptive system for synchronizing display data between a consumer node and a source node, the system comprising:

a source node configured to identifying a change in local display data, creating at least one data packet representing the change, creating at least one metadata packet identifying the at least one data packet representing the change in local display data, and transmitting the at least one metadata packet and the at least one of the identified data packets; and

a communications service in communication with the source node, the communications service configured to selecting one of the at least one metadata packet and the at least one data packet for transmission to a first consumer node.

Claim 15 (currently amended): The system of claim 14 further comprising a first consumer node; ~~wherein the first consumer node~~ configured to requests the current state of the source node local display data from the communications service.

Claim 16 (currently amended): The system of claim 15 wherein the communication service is further configured to selects one of the at least one metadata packet and the at least one data packet in response to the request made by the first consumer node.

Claim 17 (currently amended): The system of claim 15 further comprising a second consumer node, ~~wherein the second consumer node~~ configured to requests the current state of the source node local display data from the communications service.

Claim 18 (currently amended): The system of claim 17 wherein the source node is further configured to transmits a plurality of metadata packets, each of the plurality of metadata packets representing one state of the source node local display data.

Claim 19 (currently amended): The system of claim 18 wherein the communication service is further configured to selects a first metadata packet ~~to~~for transmission to the first consumer node and a second metadata packet ~~to~~for transmission to the second consumer node.

Claim 20 (currently amended): The system of claim 14 wherein the ~~consumer~~communications service further comprises a memory element.

Claim 21 (original): The system of claim 20 wherein the memory element is a persistent storage device.

Claim 22 (currently amended): The system of claim 20 wherein the ~~consumer~~communications service is further configured to stores the received at least one metadata packet in the memory element.

Claim 23 (currently amended): The system of claim 20 wherein the ~~consumer~~communications service is further configured to stores the received at least one data packet in the memory element.

Claim 24 (currently amended): The system of claim 20 wherein the ~~consumer~~communications service is further configured to stores in the memory element information regarding transmission of packets to a consumer node.

Claim 25 (currently amended): The system of claim 14 wherein the source node is further configured to encrypts the at least one data packet before transmission to the consumer node.

Claim 26 (original) A bandwidth-adaptive method for synchronizing display data between a source node and a plurality of consumer nodes, the method comprising the steps of:

- (a) identifying, by a source node, a first change in local display data;
- (b) receiving, from the source node, first metadata information identifying a first at least one data packet representing a first state of local display data;
- (c) identifying, by a source node, a second change in local display data;
- (d) receiving, from the source node, second metadata information identifying a second at least one data packet representing a second state of local display data;
- (e) generating third metadata information representing the difference between the first at least one identified data packet and the second at least one identified data packet, the third metadata information identifying a third at least one data packet;
- (f) transmitting to a consumer node the third metadata information; and
- (g) transmitting to the consumer node the third at least one data packet.